

ULTRA PREMIUM

JULY 2015

WB ACRYLIC STAIN BLOCKER

PAGE 1 OF 3



INTERIOR AND EXTERIOR



WATER WASH UP

Description

Valspar Water Based Acrylic Stain Blocker prepares your surface for your new colour whilst ensuring optimal performance of your top coat.

This product provides the benefits of a Primer, Sealer, Undercoat, and blocks stains from bleeding through your new paint. Provides sound adhesion over all interior and exterior surfaces including difficult to adhere surfaces like enamels, laminates, PVC, Zinalume®, galvanised iron and primed steel; as well as plasterboard and previously painted surfaces. Ideal for blocking oil based stains including crayon, grease, lipstick, food, pencil, markers. Also resists tannin, water, beverage and rust stains.

Why Valspar?

- | | |
|--|---|
| <ul style="list-style-type: none"> • Ideal for oil based stains • Sound adhesion over difficult to adhere surfaces • Interior and Exterior Surfaces | <ul style="list-style-type: none"> • Use with water and oil based topcoats • Quick drying • Water clean up |
|--|---|

Colours

White

Dries to a Matt finish; must be top coated.

Properties & Performance Guide

Dry & Recoat Times	<p>Touch Dry - 30 minutes</p> <p>Recoat - 2 hours</p> <p>Fully Cured - 7 days</p> <p>Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.</p>
Coverage per Coat	Up to 14 M ² /L depending on the surface texture, porosity and method of application.
Thinning	Do not thin this product.
Clean Up	<p>Clean up with soapy water away from drains.</p> <p>Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.</p>
VOC (Volatile Organic Compounds)	VOC < 20 g/Litre.

ULTRA PREMIUM

JULY 2015

WB ACRYLIC STAIN BLOCKER

PAGE 2 OF 3

Before Painting

Read safety information below before painting.

- All surfaces must be clean, dry and free of dirt, chalk, grease and grime.
- Remove residual stains from with a household cleaner and rinse clean.
- Remove old, loose or flaking paint. Sand chalky paint until sound.
- Glossy surfaces, PVC and laminate must be cleaned with sugar soap and rinsed clean. Glossy surfaces should be sanded to remove gloss before painting.
- Test soundness of previously painted surfaces. Unsound surfaces should be stripped.
- Remove all mould with a household bleach solution. Rinse thoroughly with clean water. Valspar Water Based Stain Blocking Primer will seal residual stains but will not prevent active mould growth.
- Sand bare timber smooth and remove all mill glaze.
- Ensure Zincolume®, Colorbond®, Aluminium & Galvanised Iron Sheet surfaces are clean and free of salts or other deposits. Thoroughly clean new galvanised iron sheet with a nylon scourer and detergent, then rinse. If oily, degrease with mineral turps and wipe clean.
- Allow fresh cement & concrete surfaces to fully cure; typically a 4-6 week period.
- Not suitable for set plaster. Apply one coat of Valspar Binder Sealer

Application & After Painting

- Apply when the air and surface temperatures are above 10°C and below 35°C.
- Stir contents before use with a broad paddle to ensure paint is thoroughly mixed.
- Apply full, even coats using a synthetic brush or roller or spray.
- Do not thin this product.

AFTER PAINTING

- Remove as much paint as possible from brushes and rollers before cleaning up in soapy water away from drains.
- Wipe up spills immediately with a damp cloth.

Usage Areas

Stain Type	Valspar WB Stain Blocker	Valspar OB Stain Blocker	Valspar Spirit Based Stain Blocker ¹
Water Stains	✓	✓✓✓	✓✓✓
Mould ²	✓	✓✓✓	✓✓✓
Tannin Bleed	✓✓ ³	✓✓✓	✓✓
Nicotine/Tobacco	✓	✓✓✓	✓
Smoke	✓	✓✓✓	✓✓✓
Pencil	✓✓✓	✓✓✓	✓✓
Crayon	✓✓✓	✓	✓✓
Marker	✓✓	✓✓	✓✓
Lipstick	✓✓✓	✓✓	✓✓✓
Cooking	✓✓✓	x	✓✓✓
Oil/Grease	✓✓✓	x	✓✓✓
Bitumen	✓✓	x	✓✓✓
Timber Dye Stains	✓	✓✓✓	x
Pet Stains	x	✓✓✓	✓✓✓
Odour Sealing	x	✓✓	✓✓✓

¹ For interior use only.

² Primer will seal residual stains but will not prevent active mould growth. Remove all mould with a solution of 1 part household bleach and 3 parts water. Rinse thoroughly with clean water.

³ For best tannin bleed resistance allow to dry overnight before applying finish coats.

ULTRA PREMIUM

JULY 2015

WB ACRYLIC STAIN BLOCKER

PAGE 3 OF 3

Additional Data

Available in 1, 2, 4, 10 and 15 litre containers.
Containers must be secured and stored upright during transit.
Containers must not be exposed to excessive heat or cold.
The use of proprietary additives other than those manufactured by Valspar is not recommended.

Safety Data

<p>General First Aid Instructions</p>	<p>For advice, contact the Poisons Information Centre on 131 126 (Aust), 0800 764 766 (NZ) or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled, remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.</p>
<p>General Safety Directions</p>	<p>Keep out of reach of children. Avoid contact with skin and eyes. Avoid prolonged breathing of vapour. Wash hands thoroughly after use. PROVIDE ADEQUATE VENTILATION DURING USE.</p>
<p>Further Information</p>	<p>For the latest information refer to the Safety Data Sheet available on our website or contact Valspar Customer Service. Australia Phone: 132 101 Web: www.valspar.com.au New Zealand Phone: 0800 825 7727 Web: www.valsarpaint.nz</p>

- This information is provided with respect to the listed Valspar products. Valspar Paint (Australia) recommends that:
 - You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product;
 - the product be used only in accordance with the information provided by Valspar;
 - the product be transported and handled in accordance with the SDS and relevant TDS; and
 - you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.
- Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.
- To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Valspar is a registered trademark of The Valspar Corporation, USA

VALSPAR CUSTOMER SERVICE: Ph: 132 101 (AUSTRALIA) – Ph: 0800 825 7727 (NEW ZEALAND)