

ULTRA PREMIUM

RESOURCE CODE 51356-LINE

NOVEMBER 2013

OIL BASED TRIM ENAMEL SATIN

PAGE 1 OF 3



INTERIOR



TINTABLE



TURPS

Description

Valspar Ultra Premium Trim Enamels are designed to make your painting project a more positive experience. Let Valspar help you create a space you can't wait to get home to.

Valspar Oil Based Trim Satin Enamel is a smooth enamel coating designed to protect and decorate your home and is ideal for covering interior trim surfaces. It provides complete protection.

Why Valspar?

- | | |
|---|---|
| <ul style="list-style-type: none"> • Interior Only • Even smooth & tough finish | <ul style="list-style-type: none"> • Excellent washability and scuff resistance • Superior covering power |
|---|---|

Colours

White, Light, Mid and Strong bases; selected factory colours. Tint using Ecotint® to Valspar colours or other competitor colours.

Dries to a Satin finish

Properties & Performance Guide

Dry & Recoat Times	<p>Touch Dry - 4 hours</p> <p>Recoat - 24 hours</p> <p>Fully Cured - 7 days</p> <p>Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.</p>
Coverage per Coat	Up to 16 M ² /L depending on the surface texture, porosity and method of application.
Thinning	Thinning is generally not required. If necessary to aid spray atomisation, thin with up to 5% mineral turps.
Clean Up	Clean up with mineral turps away from drains. Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 450g/Litre.

ULTRA PREMIUM

RESOURCE CODE 51356-LINE

NOVEMBER 2013

OIL BASED TRIM ENAMEL SATIN

PAGE 2 OF 3

Before Painting

Read safety information below before painting.

- Sound preparation is the key to a perfect finish.
- The surface must be clean, dry and free of dirt, dust, chalk, grease and grime.
- Glossy surfaces should be sanded to remove gloss before painting.
- Remove old, loose or flaking paint.
- Repair all damaged areas and sand smooth.
- Test soundness of previously painted surfaces. Unsound surfaces should be stripped for best results.
- Some primers used on pre-primed timbers are of poor quality. Unless a painting specification is supplied by the timber manufacturer, pre-primed timber should be sanded back to bare before coating to ensure durability.
- If mould is present, it must be completely removed. Apply a solution of 1 part household bleach and 3 parts water. Rinse thoroughly with clean water. Allow to dry.

Application & After Painting

- Apply when the air and surface temperatures are above 10°C and below 35°C.
- Stir contents before use with a broad paddle to ensure paint is thoroughly mixed.
- Check your colour is correct, as tinted paint is not refundable.
- When more than one container of the same colour is required, intermix containers to ensure colour uniformity. If you feel that you may run out of paint, stop at a natural break.
- Apply 2 full, even coats using a premium quality brush or roller or spray. Apply liberally, working from dry areas into the paint's wet edge and finish with long, gentle strokes. Avoid excessive rolling or brushing.

AFTER PAINTING

- Remove as much paint as possible from brushes and rollers before cleaning up in mineral turps away from drains.
- Wipe up spills immediately with a damp cloth.
- **Soak all contaminated cloths in water after use or they may self ignite**
- Allow at least 1 week for finish to harden before washing. Only use a mild detergent and water.

Important:

All oil based enamels can yellow under certain conditions. Valspar Water Based Trim Enamels are non yellowing. Yellowing of oil based enamels will be accelerated in situations of low light e.g. sliding cavity doors or behind pictures. Other factors that can reduce excessive yellowing in the application period are:

1. Ensure maximum ventilation.
2. Avoid applying water-based paint in the vicinity of the new oil based enamel work.
3. Avoid using ammonia based household cleaners for a minimum of two weeks after applying the enamel.

Usage Areas

Usage	Preparatory Coats
Previously painted surfaces	Apply one coat of Valspar Oil Based Primer Sealer Undercoat.
Interior Bare timber and Hardboard (not MDF)	Apply one coat of Valspar Oil Based Primer Sealer Undercoat.
Interior MDF	Apply one coat of Water Based Valspar Primer Sealer Undercoat.
New set plaster & Masonry	Apply one coat of Valspar Binder Sealer. Then apply one coat of Valspar Oil Based Primer Sealer Undercoat.

ULTRA PREMIUM

RESOURCE CODE 51356-LINE

NOVEMBER 2013

OIL BASED TRIM ENAMEL SATIN

PAGE 3 OF 3

Additional Data	
<p>Available in 500mL, 1, 4 and 10 litre containers. Tinted paint is non refundable, so choose your colours carefully and check that the colour is correct in all cans. Containers must be secured and stored upright during transit. Containers must not be exposed to excessive heat or cold. The use of proprietary additives other than those manufactured by Valspar is not recommended.</p>	

Safety Data	
General First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Aus), 0800 764 766 (NZ), or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If vapour is inhaled, remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
General Safety Directions	HAZARDOUS - Contains 30-60% liquid hydrocarbons. Flammable. Keep away from sources of ignition. No smoking. Keep closed when not in use. Keep out of reach of children. Irritating to skin and eyes. Avoid contact with skin and eyes - wear suitable protective clothing. Avoid prolonged breathing of vapour. Wash hands thoroughly after use. PROVIDE ADEQUATE VENTILATION DURING USE.
Further Information	For the latest information refer to the Safety Data Sheet available on our website or contact Valspar Customer Service. Australia Phone: 132 101 Web: www.valspar.com.au New Zealand Phone: 0800 735 551 Web: www.valspar.co.nz

- This information is provided with respect to the listed Valspar products. Valspar Paint (Australia) recommends that:
 - You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product;
 - the product be used only in accordance with the information provided by Valspar;
 - the product be transported and handled in accordance with the SDS and relevant TDS; and
 - you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.
- Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.
- To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Valspar is a registered trademark of The Valspar Corporation, USA

VALSPAR CUSTOMER SERVICE: Ph: 132 101 (AUSTRALIA) – Ph: 0800 735 551 (NEW ZEALAND)